



D-sub connectors require a space of 100mm

position of D-sub connectors

Active Vibration Isolation Platform SW1000-6.0

- dimensions: 1000x800x130mm
- weight: 135kg
- maximum load capacity: 900kg
- material of housing: aluminum
- surface: anodized
- configuration: 6 internal isolation elements (24 sensor/actuator pairs)
- electronics: 2-channel controller & 4-channel controller
- cables: 6 D-sub cables (3m long)

| | | | | | | | | | |
|--------------|------------|---------------------------------|------|--|--|--|--|----------|--|
| | | Allgemein-toleranzen ISO 2768-f | | Werkstück-kanten DIN ISO 13715 | | Werkstoff: | | Maßstab: | |
| | | Datum | | Name | | Active Vibration Isolation Platform SW1000-6.0 and Controller | | | |
| Gezeichnet | | 21.04.2010 | | U. Stöbener | | | | | |
| Kontrolliert | | | | | | | | | |
| Norm | | | | | | Zeichnungs-Nr.: | | | |
| Artikel-Nr.: | | | | | | | | | |
| Status | Änderungen | Datum | Name | F:\CAD\Technische Zeichnungen\MOD-Sandwich Zeichnungen\Standard 1000x800\SW1000_6_Controller.idw | | | | | |

A3